

Beaumont Fire-Rescue Services

PERFORMANCE BENCHMARKS

407.06I

Applying the RIG Emergency Air Supply-Face Piece Only (cyl psi above 1000)

Discipline: R.I.G.
Effective: 6/5/2009
Revised:
Replaces:

Anne Huff, Fire Chief

I. Objective

The examinee shall properly replace the downed firefighters face piece with a RIG face piece.

II. Instructions – Procedures for Achieving the Objective

Given a RIG pack, you will have to correctly change out the downed firefighter's face piece with the RIG's face piece using the proper procedures and methods. The air supply shall be above 1000psi. You will begin on my instruction to start. The skill will end when you have successfully changed out the face piece. Do you understand these instructions?

III. Examiner's Note

The examinee will not be able to review the performance steps prior to testing. The downed firefighter shall be in place for the skill prior to admitting the examinee into the test area. Neither the RIG pack nor the SCBA shall be touched by the examinee prior to the start of testing.

IV. Preparation & Equipment

- A. Person to act as the downed firefighter
- B. Personnel protective equipment
- C. SCBA
- D. RIG pack

V. Reference Sources

- A. NFPA 1407, Training Fire Service Rapid Intervention Crews.
- B. NFPA 1404, Fire Service Respiratory Protection Training

407.061 – Applying the RIG Emergency Air Supply-Face Piece Only (cylinder psi above 1000)

Discipline: R.I.G.

Name: _____ Officer #: _____
 Evaluator: _____ Officer #: _____
 Date: _____ Location: _____

If the firefighter: (No partial points given)

- a) Determines integrity of downed firefighter’s face piece..... **P/F** _____
- b) Attempts to move downed firefighter from an IDLH atmosphere to a safe area while protecting the compromised face piece (i.e.; opens bypass valve to create positive pressure inside face piece, uses gloved hand, etc.) 1.0 _____
- c) Removes face piece from RIG bag 1.0 _____
- d) Removes downed firefighter’s helmet 1.0 _____
- e) Pulls hood back (does not remove it) to visualize face piece straps 1.0 _____
- f) Disconnects low pressure regulator (MMR)..... 1.0 _____
- g) Doffs compromised face piece and don RIG bag face piece 1.0 _____
- h) Tightens straps to secure face piece seal 1.0 _____
- i) Connects low pressure regulator (MMR), verifies air flow..... **P/F** _____
- j) Replaces downed firefighter’s protective hood 1.0 _____
- k) Replaces downed firefighter’s helmet 1.0 _____
- l) Verbalizes RIG bag SCBA cylinder pressure **P/F** _____

Note: Attach this page to the first.

Points Possible	Passing Score	Attempt	Performance Rating (Points)	PASS	FAIL
9	7	First			
		Second			
		Third			